

Phosphoric acid (asPO ₄ ³⁻), %	1.0max
pH (1% water solution)	9.5-10.5
Density (20°C), g/cm ³	1.25min
Chloride(Cl ⁻), %	3.0max

Usage:

[EDTMPS](#) can be used as corrosion inhibitor in circulating cool water system and boiler water. It is a chelating agent in non-cyanogen electroplating industry and a water-softening agent in printing & dyeing industry. When used alone, 2~10mg/L is preferred. When built with [HPMA](#) by ratio EDTMP:HPMA=1:3, it can be used for low pressure boiler. It can also be built with BTA, [PAAS](#) and zinc salt.

Package and Storage:

200L plastic drum,IBC(1000L),customers' requirement. Storage for ten months in shady room and dry place.

Synonyms:

[EDTMPS](#); [EDTMP](#); [EDTMPA](#); [Ethylene Diamine Tetra \(Methylene Phosphonic Acid\) Sodium Salt](#); [EDTPO](#); [ETHYLENEDIAMINE TETRA\(METHYLENEPHOSPHONIC ACID\)](#)

Contact Us

TEL: +86-632-3671188

E-mail: export@krchemical.com

Website: kairuiwater.com | krwater.com | krwater.net

ADD: No.1, Fuqian South Road, Xuecheng Chemical Industrial Park, Xuecheng District,

Zaozhuang City, Shandong Province, China